

# PRODUCT DATASHEET

## ULTRA LED™ Glass PAR Lamps 11W PAR30LN DIM 5000K FL 40 1PK

SYLVANIA ULTRA LED™ PAR Lamps | ULTRA LED PAR Lamps



### Areas of application

- Downlights, pendant fixtures, table lamps, wall sconces
- Healthcare, hospitality, residential, retail

### Product features

- Longer life than traditional halogen lamps
- Glass body with full optics – similar to halogen PAR lamps
- CRI of 80 ensures good color definition
- RoHS compliant, mercury and lead free
- Dimmable down to 10 %
- Wet rated



## TECHNICAL DATA

### Additional product data

Base	E26
Mercury content	0.0 mg
Mercury-free	Yes
Ordering Abbreviation	LED11PAR30LNDIM850FL4013YGLWRP
Abbrev. With Packaging Info.	LED11PAR30LNDIM850FL4013YGLWRP 6/CS 1/SK
UPC Code	0046135746031
NAED	74603
Family Brand Name	ULTRA GLASS
General Description	LED PAR30 LN, 11W, Dimmable, 82CRI, 850 Lumen, 5000K, 15000 Life,E26Medium Base

### Electrical data

Nominal Wattage	11.00 W
Nominal voltage	120.00 V
Claimed Equivalent Lamp Pwr	75 W
Type of current	AC
Centerbeam Candlepower (cp)	1,375 cd

### Photometrical data

Lumens	850 lm
Efficacy	77
Color Temperature/CCT	5000 K
Color Rendering Index (CRI)	82
Light color	850

### Dimensions & Weight

Overall length	116.99 mm
Diameter	95.00 mm
Product weight	220.00 g

### Materials & Colors

Lamp Finish	Silver
Bulb	PAR30LN
Bulb Glass Type	HARDGLASS

## Application & Mounting

Dimming	Yes
---------	-----

## Temperatures & operating conditions

Ambient temperature range	-20...+45 °C
---------------------------	--------------

## Lifespan

Average Rated Life (hr)	15000
-------------------------	-------

## Capabilities

Dimming	Yes
---------	-----

## Certificates & Standards

Type of protection	IP66
Certification Listing	RoHS / CSA / FTC / FCC / cULus

## Country-specific categorizations

Order reference	SILV 11W/850 12
-----------------	-----------------

## Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	E26
Length	116.99 mm
Height	95.00 mm
Width	95.00 mm

## Safety advice

- Suitable for wet locations.
- -4°F to +113°F (-20°C to +45°C)
- Not for use with emergency light fixtures or exit lights.
- Approved for use in enclosed fixtures.

## DOWNLOAD DATA

Spec Sheets and Product Documents	Document name
 Product Family Spec Sheet	ULTRA LED Glass PAR Lamps

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.