




ENERGY SAVING REPLACEMENTS FOR FLUORESCENT T8. Every size and installation method you need — in the highest quality, best light output design.

- 9W and 12W models
- Available in 2 FT and 3 FT
- 3500K, 4000K, and 5000K CCT options
- Beautiful uniform illumination from our glass construction
- Frosted lens softens the light output
- Approved for installation in completely enclosed fixtures



									
ALSO WORKS ON 208V & 240V	GLASS CONSTRUCTION	CRI 80+	BEAM ANGLE 240°	LIGHT DISTRIBUTION 330°	BALLAST BYPASS UL TYPE B	DOUBLE-ENDED POWER	OPERATING TEMP -40°F TO 113°F	50,000hrs RATED LIFE L70	

PART #	UPC	REPLACES	WATTAGE	LUMENS	CCT	LENGTH	BASE	DLC CODE
LED-9T8-835DE24-G3	844006022860	17W	9W	1100	3500K	2 FT	G13	PLASS715ZPE1
LED-9T8-840DE24-G3	844006022877			1150	4000K			PLEVKFK911PU
LED-9T8-850DE24-G3	844006022884			5000K	PLW4TU6Y2QIT			
LED-12T8-835DE36-G3	844006022907	25W	12W	1400	3500K	3 FT		PLQQKIE4YDD0
LED-12T8-840DE36-G3	844006022914			1450	4000K			PLY0S99SZY00
LED-12T8-850DE36-G3	844006022921			5000K	PLAU8Y96O653			

