

NOXAC-5632TW

5"/6" AC Onyx LED Retrofit Baffle with Selectable CCT

Source: 1150lm
16.5W

PRODUCT DESCRIPTION

5"/6" AC Onyx Retrofit Series requires no driver and allow for a sleek design. Spun aluminum construction provides clean sharp edges and is suitable for use with most 5" and 6" recessed housings. Deep regressed optics and round aperture deliver even and glare-free illumination.

FEATURES

- Delivering over 1150 lumens
- Five color temperatures in each fixture (2700K / 3000K / 3500K / 4000K / 5000K)
- Dimmable AC LED
- Includes medium base socket adaptor for easy retrofitting in 5" or 6" recessed housings
- 5-year limited warranty
- Classified for wet locations

SPECIFICATION

Reflector: One piece, spun aluminum construction dissipates heat and extends life. Unitized Thermal Management, UTM, provides exceptional cool operation.

Mounting: Two steel, torsion mounting springs allow for easy and secure mounting in most 5" and 6" housings.

Retrofit: Luminaires include a medium base screw-socket adaptor ([NRA-21ISM](#)) for retrofitting into medium base downlight housings. Intended to be used as a LED lamp replacement. GU24 socket adaptor ([NRA-212SM](#)) is available.

ELECTRICAL

Voltage: 120VAC

Lumens / Wattage: 1150lm / 16.5W

Color Temperature: Selectable CCT: 2700K / 3000K / 3500K / 4000K / 5000K (*Note: Preset to 3000K*)

Color Rendering Index: 90+ CRI

Operating Temperature: 0°C to 25°C ambient temperature

Dimming: Triac/ELV

[Click Here](#) or check complete dimmer list at [www.](#)

NoraLighting.com in the "Compatibility" page under "Resources" tab

COMPATIBLE HOUSINGS

Onyx retrofits are compatible with most 5" & 6" IC and Non-IC housings by Nora and others.

Fire Box

[NFBIC-5INCATA](#)

[NFBIC-5LMRATA*](#)

[NFBIC-6INCATA](#)

[NFBIC-6LMRATA*](#)

New Construction

[NHIC-5LMRAT*](#)

[NHIC-5LMRAT/277*¹](#)

[NHIC-527LMRAT*](#)

[NHIC-501QAT](#)

[NHIC-527QAT](#)

[NHIC-6LMRAT*](#)

[NHIC-6LMRAT/277*¹](#)

[NHICCP-6LMRAT*](#)

[NHIC-27LMRAT*](#)

[NHIC-17QAT](#)

[NHIC-17QNBAT](#)

[NHIC-27QAT](#)

[NH-26Q](#)

[NHIC-6G24ATFL](#)

Remodel

[NHRIC-5LMRAT*](#)

[NHRIC-527LMRAT*](#)

[NHRIC-504QAT](#)

[NHRIC-527QAT](#)

[NHRIC-6LMRAT*](#)

[NHRIC-27LMRAT*](#)

[NHRIC-17QAT](#)

[NHRIC-17QNBAT](#)

[NHRIC-27QAT](#)

[NHR-26Q](#)

* Nora LED Dedicated housings are listed for use only with Nora LED Retrofits.

¹ Housings include a step down transformer

ACCESSORIES

[NEPK-23LEDUNV](#): 23W Emergency with Remote Test Switch

[NEPKA-20/23LEDRTS](#): Ribbon Test Switch for NEPK-23LEDUNV

TAGS AND LISTINGS

- cETLus classified for Wet Locations
- [5-Year Limited Warranty](#)
- Meets ASTM 283 Airtight requirements
- FCC compliant
- Certified to the high efficacy requirements of California Title 24 JA8-2025



Type

Project

Catalog No.

Notes

Performance Data

Part Number	Lumens	CCT
NOXAC-5632TWWW	1037lm	2700K
NOXAC-5632TWWW	1089lm	3000K
NOXAC-5632TWWW	1175lm	3500K
NOXAC-5632TWWW	1169lm	4000K
NOXAC-5632TWWW	1113lm	5000K

PRODUCT IMAGES AND DIMENSIONS



5"/6" AC Onyx LED Retrofit Baffle with Selectable CCT

Finish

NOXAC-5632TWWW = White Finish

Optional Accessories

Description

NRA-21ISM = Medium base screw-in socket (included w/ each)

NRA-212SM = Socket adapter for use with GU24 housings

NEPK-23LEDUNV = 23W Emergency LED Driver w/ Remote Test Switch

NEPKA-20/23LEDRTS = Ribbon Test Switch for NEPK-23LEDUNV

Example: **NOXAC-5632TWWW** = 5"/6" AC Onyx LED Round Retrofit Baffle with Selectable CCT, White Baffle / White Flange