

NTLE-875

4' Track Pack with (3) MAC XL LED Track Heads
Source: 18W LED per head
Up to 1250lm per head

PRODUCT DESCRIPTION

Track pack comes complete and ready to install with mounting hardware and track heads. Components includes: (1) 4' single circuit track, (2) end caps, (1) floating canopy feed and (3) MAC XL LED track heads. The utilitarian style fits almost any design criteria.

FEATURES

- Over 75% energy savings when compared to incandescent
- 4' Track Pack includes all hardware and ready to install
- Black, silver or White finish
- Up to 1250lm / 18W LED output per head
- Field adjustable beam spreads (Flood installed and spot included)
- 2700K, 3000K, 3500K or 4000K @ 90 CRI
- Dimmable
- Easily to longer lengths or additional track heads
- 5-Year Limited Warranty

CONSTRUCTION

Housing: Die-cast aluminum construction dissipates heat for longer life.

Adjustability: 350° horizontal and 90° vertical adjustment

ELECTRICAL

Input Voltage: 120V

Lumens / Wattage Per Head: Up to 1250lm / 18W

Color Temperature: 2700K 3000K, 3500K or 4000K

Color Rendering Index: 90+ CRI

Beam Spread: 56° Flood installed and 24° spot included

Lifetime: 44,000 hours @ L70

Dimming: ELV

[Click Here](#) or check complete dimmer list at www.NoraLighting.com in the "Compatibility" page under "Resources" tab

One / Two Circuit Conversion: Positive contact (opposite neutral and ground contacts) is preset to "down" position at factory, but may be raised to the higher position to install onto the second circuit of Nora Lighting NT-2300 series two-circuit track.

LABELS AND LISTINGS

- cULus Listed for dry locations
- [5-Year Limited Warranty](#)



Type	
Project	
Catalog No.	
Notes	

Performance Data Per Head		
Part Number	Lumens	CCT
NTLE-875927	1069lm	2700K
NTLE-875930	1211lm	3000K
NTLE-875935	1232lm	3500K
NTLE-875940	1252lm	4000K
Delivered lumens will vary depending on beam spread and finish		

PRODUCT IMAGE



NTLE-875B



NTLE-875S



NTLE-875W

4' Track Pack with (3) MAC XL LED Track Heads

Series	Color Temperature	Finish
NTLE-875 = 4' Track Pack with (3) MAC XL LED Track Heads	927 = 2700K	B = Black
	930 = 3000K	S = Silver
	935 = 3500K	W = White
	940 = 4000K	

Example: NTLE-875927B = 4' Track Pack with (3) MAC XL LED Track Heads, 2700K / 90 CRI, Black Finish

PHOTOMETRICS

MAC XL LED Track Head

Type


Project

Catalog No.

Notes

Test Information

Test Number: NTR11020
Part Number: NTE-875L940X18W
Beam Spread: 25° Spot
Lumens: 1252lm
Wattage: 17W
Efficacy: 73lpw
CCT / CRI: 4000K / 90 CRI
Spacing Criteria (0°-180°): 0.44
Spacing Criteria (90°-270°): 0.44



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	279fc	1'-10"
6'	124fc	2'-8"
8'	69.7fc	3'-7"
10'	44.6fc	4'-6"
12'	31fc	5'-5"

Zonal Lumen Summary


Zone	Lumens	% Luminaire
0-30	1031	82.4
0-40	1127	90
0-60	1214	97
0-90	1242	99.2
90-180	9	0.8
0-180	1252	100

Candela Table

Vertical Angles	Candela
0	4460
5	4037
15	1633
25	476
35	146
45	68

Test Information

Test Number: NTR11021
Part Number: NTE-875L940X18W
Beam Spread: 48° Flood
Lumens: 1251lm
Wattage: 17.48W
Efficacy: 72lpw
CCT / CRI: 4000K / 90 CRI
Spacing Criteria (0°-180°): 0.76
Spacing Criteria (90°-270°): 0.76



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	105fc	3'-6"
6'	46.7fc	5'-4"
8'	26.2fc	7'
10'	16.8fc	8'-10"
12'	11.7fc	10'-7"

Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	862	68.9
0-40	1067	85.3
0-60	1209	96.6
0-90	1246	99.6
90-180	5	0.4
0-180	1251	100

Candela Table

Vertical Angles	Candela
0	1680
5	1636
15	1306
25	769
35	321
45	124

Lumen Output Multipliers

Color Temperature: 2700K (0.84), 3000K (0.95), 4000K (1.00)