



Project / Job Name:

Location:

Fixture Type:

Notes:

S11556 - 5.5 Watt; 2GX7 Base; 27K/30K/35K/40K CCT Selectable; Frost Finish; Ballast Bypass; 120-277 Volt



GENERAL

Company	SATCO
EA Height	6.61
EA Width	0.91
EA Length	1.54
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Lamp Filament	LED
Material	Polycarbonate (PC)
Status	Active
Style	Transitional
Surge Protection	Built-in-surge protection - 0.5KV
Total Harmonic Distortion	20%
CCT Selectable	True
Wattage Selectable	False
Finish Family	White
Amps	0.046-0.020A
Has Camera	False
IOT Enabled	False
Operating Position	Universal
Power Factor	0.9
SDS Class	LED_Lamp
Indoor Outdoor	Indoor
Product Technology	LED
Fluor Equiv	13W

ELECTRICAL

CCT (Kelvin Temp)	2700K/3000K/3500K/4000K
Dimmable	Non-Dimmable
Hours Rated	50000
Beam Angle (degree)	120
Color Temp	Warm to Cool White
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-20C (-4F) to +45C (+113F)
Lumens	600L/620L/630L/650L
Volts	120V-277V
Watts	5.5W

PHYSICAL

Lamp Base	2GX7 (4-Pin)
Finish	Frost
Housing Color	White
ANSI Base	2GX7
Lamp Type	PL
MOD Lamps	1.26
MOL	6.51

ADDITIONAL INFO

Warranty	5-Years
Rated For Enclosed Fixture	False

PACKAGING

UPC	045923115561
Case Cube	0.45
Case Height	5.71
Case Length	18.11
Case Quantity	50
Case UPC	10045923115568
Case Weight	6.8
Case Width	7.52
EA Cube	0.0054
EA Height	6.61
EA Length	1.54
EA Quantity	1
EA Weight	0.1
EA Width	0.91
Inner Cube	0.0683
Inner Height	3.46
Inner Length	6.93
Inner Quantity	10
Inner UPC	20045923115565
Inner Weight	1.0
Inner Width	4.92
Pack Type	Box
Web Length	6.51
Web Width	1.26

COMPLIANCE

CA Regulations	Exempt - Base Not Regulated
CA Status	Lawful for sale in California
FCC Compliant	True
Location Rating	Damp
NSF Approved	No
ROHS Compliant	Yes
Safety Listing	cULus - Classified
CA Compliance Text	Lawful for sale
DLC Approved	False
Title 20	Exempt
T24 Compliant	False