

C023-A C034-A

LED Ceiling Light



Features

Housing

Injection Molded Polycarbonate Housing and Shade
Ideal for High Humidity Environment Applications
IP65 Rated
Suitable for Ceiling Mount or Wall Mount

Optical

Shade: Injection Molded High Transmission Opal Polycarbonate Creates Excellent Light Distribution and Uniformity

Electrical

High Power Factor, Low THD
Option: Built-in Emergency Battery Backup (-EM)
Bi-Level Light with Built-in High Frequency Motion Sensor (-BI)

Lamp

Built-in LED Module
MCT Type: Adjustable Multi Color Temperature 3000K/4000K/5000K

Certification

ETL/cETL Listed, Wet Location Rated

Warranty

5 Years Warranty on Driver and LED Module



LED Type

Model	Input Voltage	Input Wattage	CRI	Lumen (TYP)	CT	Dimension (OD X H)
C023-65-A-MCT	120V ~ 277V	23W	>80	2100	3000K/4000K/5000K	14.3" x 4.33"
C023-65-A-xxxxK	120V ~ 277V	23W	>80	2100	3000K, 3500K, 4000K, 5000K	14.3" x 4.33"
C034-65-A-xxxxK	120V ~ 277V	34W	>80	3300	3000K	17.7" x 4.33"