

PRODUCT DATASHEET

LED A19 5.5W DIM FR 3000K 1PK

SYLVANIA ULTRA A19 Lamps | Dimmable ULTRA A19 LED lamps with 80+ CRI and 15,000-hour rated life



Areas of application

- Downlights, pendant fixtures, table lamps, wall sconces
- Healthcare, hospitality, residential, retail
- Indoor and outdoor
- Suitable for rough service

Product features

- 15,000 hours lifetime (L70)
- RoHS compliant, mercury and lead free
- UV and IR free
- Reduces energy consumption up to 85 %
- Last up to 20 times longer than incandescent lamps



- No warm-up time, instant-on with full light output and stable color
- Dimmable down to 10 %
- Approved for enclosed fixtures

TECHNICAL DATA

Additional product data

Base	E26
Mercury content	0.0 mg
Mercury-free	Yes
Ordering Abbreviation	LED5.5A19DIMO830URP
Abbrev. With Packaging Info.	LED5.5A19DIMO830URP 6/CS 1/SKU
UPC Code	0046135743986
NAED	74398
Family Brand Name	ULTRA
General Description	LED A19, 5.5W, Dimmable, 80CRI, 450 Lumen, 3000K, 15000 Life, E26 Medium Base, FROSTED Finish

Electrical data

Nominal Wattage	5.50 W
Nominal voltage	120.00 V
Claimed Equivalent Lamp Pwr	40 W
Type of current	AC
Supply Frequency	50...60 Hz

Photometrical data

Lumens	450 lm
Efficacy	82
Light color (designation)	Warm White
Color Temperature/CCT	3000 K
Color Rendering Index (CRI)	80
Light color	830

Dimensions & Weight

Overall length	107.01 mm
Diameter	59.99 mm
Product weight	59.99 g

Materials & Colors

Lamp Finish	Frosted
Bulb	A19

Bulb Glass Type	PLASTICS
-----------------	----------

Application & Mounting

Dimming	Yes
---------	-----

Temperatures & operating conditions

Ambient temperature range	-20...+45 °C
---------------------------	--------------

Lifespan

Average Rated Life (hr)	15000
-------------------------	-------

Capabilities

Dimming	Yes
---------	-----

Certificates & Standards

Certification Listing	CSA / FTC / FCC / cULus / RoHS
Energy Star Rated	X

Country-specific categorizations

Order reference	LED5.5A19DIMO83
-----------------	-----------------

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	E26
Length	107.01 mm
Height	59.99 mm
Width	59.99 mm

Safety advice

- Suitable for damp locations.
- Not for use with emergency light fixtures or exit lights.
- -4°F and + 113°F (-20°C and +45°C)

DOWNLOAD DATA

Spec Sheets and Product Documents	Document name
 Product Family Spec Sheet	ULTRA LED A-line Lamps

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.