

# PRODUCT DATASHEET

## ULTRA LED A21 23W DIM FR 2700K 1PK

SYLVANIA ULTRA A19 Lamps | Dimmable ULTRA A19 LED lamps with 80+ CRI and 15,000-hour rated life



---

### Areas of application

- Downlights, pendant fixtures, table lamps, wall sconces
- Healthcare, hospitality, residential, retail
- Indoor and outdoor
- Suitable for rough service

---

### Product features

- 15,000 hours lifetime (L70)
- RoHS compliant, mercury and lead free
- UV and IR free



- Reduces energy consumption up to 85 %
- Last up to 20 times longer than incandescent lamps
- No warm-up time, instant-on with full light output and stable color
- Dimmable down to 10 %
- Approved for enclosed fixtures

## TECHNICAL DATA

### Additional product data

Base	E26
Mercury content	0.0 mg
Mercury-free	Yes
Ordering Abbreviation	LED23A21DIMO827URP
Abbrev. With Packaging Info.	LED23A21DIMO827URP 6/CS 1/SKU
UPC Code	0046135797149
NAED	79714
Family Brand Name	ULTRA
General Description	LED A21, 23W, Dimmable, 80CRI, 2600 Lumen, 2700K, 15000 Life, E26 Medium Base, FROSTED Finish

### Electrical data

Nominal Wattage	23.00 W
Nominal voltage	120.00 V
Claimed Equivalent Lamp Pwr	150 W
Supply Frequency	50...60 Hz

### Photometrical data

Lumens	2600 lm
Efficacy	113
Color Temperature/CCT	2700 K
Color Rendering Index (CRI)	80
Light color	827

### Dimensions & Weight

Overall length	138.40 mm
Diameter	74.50 mm
Product weight	190.00 g

### Materials & Colors

Lamp Finish	Frosted
Bulb	A21
Bulb Glass Type	PLASTICS

### Application & Mounting

Dimming	Yes
---------	-----

**Lifespan**

Average Rated Life (hr)	15000
-------------------------	-------

**Capabilities**

Dimming	Yes
---------	-----

**Certificates & Standards**

Certification Listing	RoHS / CSA / FTC / FCC / cULus
Energy Star Rated	X

**Country-specific categorizations**

Order reference	23W/827 120V 6X
-----------------	-----------------


**Energy labelling regulation data acc EU 2019/2015**

Light source cap-type (or other electric interface)	E26
Length	138.40 mm
Height	74.50 mm
Width	74.50 mm

**Safety advice**

- Suitable for damp locations.
- Not for use with emergency light fixtures or exit lights.
- -4°F and + 113°F (-20°C and +45°C)

**DOWNLOAD DATA**

Spec Sheets and Product Documents	Document name
 Product Family Spec Sheet	ULTRA LED A-line Lamps

**DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.