



PRODUCT DATASHEET

LED 8.5W FR 5000K 2PK

SYLVANIA Contractor Series A19/A21 Lamps | SYLVANIA Contractor Series are rated for up to 11,000 hours



Areas of application

- Downlights, pendant fixtures, table lamps, wall sconces
- Healthcare, hospitality, residential, retail
- Suitable for rough service

Product features

- Reduces energy consumption up to 86 %
- 11,000 hours lifetime (L70)
- No warm-up time, instant-on with full light output and stable color



TECHNICAL DATA

Additional product data

| | |
|------------------------------|--|
| Base | E26 |
| Mercury content | 0.0 mg |
| Mercury-free | Yes |
| Ordering Abbreviation | LED8.5A19F85010YVRP2 |
| Abbrev. With Packaging Info. | LED8.5A19F85010YVRP2 12/CS 2/SKU |
| UPC Code | 0046135792823 |
| NAED | 79282 |
| Family Brand Name | 10YV |
| General Description | LED A19 8.5W,80CRI,800 Lumen, 5000K,11000 life |

Electrical data

| | |
|-----------------------------|------------|
| Nominal Wattage | 8.50 W |
| Nominal voltage | 120.00 V |
| Claimed Equivalent Lamp Pwr | 60 W |
| Supply Frequency | 50...60 Hz |

Photometrical data

| | |
|-----------------------------|----------|
| Lumens | 800 lm |
| Efficacy | 94 |
| Light color (designation) | Daylight |
| Color Temperature/CCT | 5000 K |
| Color Rendering Index (CRI) | 80 |
| Light color | 850 |

Dimensions & Weight

| | |
|----------------|-----------|
| Overall length | 110.01 mm |
| Diameter | 59.99 mm |
| Product weight | 50.00 g |

Materials & Colors

| | |
|-----------------|----------|
| Lamp Finish | Frosted |
| Bulb | A19 |
| Bulb Glass Type | PLASTICS |

Application & Mounting

| | |
|---------|----|
| Dimming | No |
|---------|----|

Temperatures & operating conditions

| | |
|---------------------------|--------------|
| Ambient temperature range | -20...+40 °C |
|---------------------------|--------------|

Lifespan

| | |
|-------------------------|-------|
| Average Rated Life (hr) | 11000 |
|-------------------------|-------|

Capabilities

| | |
|---------|----|
| Dimming | No |
|---------|----|

Certificates & Standards

| | |
|-----------------------|---------------------------------|
| Certification Listing | RoHS / CSA / FTC / FCC / cETLus |
|-----------------------|---------------------------------|

Country-specific categorizations

| | |
|-----------------|-----------------|
| Order reference | 8,5W/850 120V 6 |
|-----------------|-----------------|


Energy labelling regulation data acc EU 2019/2015


| | |
|---|-----------|
| Light source cap-type (or other electric interface) | E26 |
| Length | 110.01 mm |
| Height | 59.99 mm |
| Width | 59.99 mm |

Safety advice

- Suitable for damp locations.
- Non-dimmable.
- -4°F and +104°F (-20°C and +40°C)
- Approved for use in totally enclosed fixtures.

DOWNLOAD DATA

| Spec Sheets and Product Documents | | Document name |
|--|---------------------------|---------------------------------|
|  | Product Family Spec Sheet | Contractor Series LED A19 Lamps |

| Photometric and lighting design files | | Document name |
|--|----------------|--|
|  | IES file (IES) | LED A19, 8.5W 80CRI, 800 Lumen, 5000K IE FILES |

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.