

PRODUCT DATASHEET

Contractor Series LED PAR Lamps 9W PAR30LN 3000K FL 45 2PK

SYLVANIA Contractor Series PAR Lamps | PAR Lamps rated up to 11,000 hours life



Areas of application

- Downlights, pendant fixtures, table lamps, wall sconces
- Healthcare, hospitality, residential, retail

Product features

- Beam angle: 45°
- 11,000 hours lifetime (L70)
- RoHS compliant, mercury and lead free
- No warm-up time, instant-on with full light output and stable color
- Reduces energy consumption up to 88 %
- Lasts 4 times longer than halogen lamps
- 3-year limited warranty



TECHNICAL DATA

Additional product data

Base	E26
Mercury content	0.0 mg
Mercury-free	Yes
Ordering Abbreviation	LED9PAR30LN830FL4510YVRP2
Abbrev. With Packaging Info.	LED9PAR30LN830FL4510YVRP2 12/CS 2/SKU
UPC Code	0046135792809
NAED	79280
Family Brand Name	10YV
General Description	LED PAR30LN, 9W 82CRI, 800 Lumen, 3000K, 11000 life

Electrical data

Nominal Wattage	9.00 W
Nominal voltage	120.00 V
Claimed Equivalent Lamp Pwr	65 W
Centerbeam Candlepower (cp)	900 cd

Photometrical data

Lumens	800 lm
Efficacy	89
Color Temperature/CCT	3000 K
Color Rendering Index (CRI)	82
Light color	830

Dimensions & Weight

Overall length	112.00 mm
Diameter	95.00 mm
Product weight	105.00 g

Materials & Colors

Bulb	PAR30LN
Bulb Glass Type	PLASTICS

Application & Mounting

Dimming	No
---------	----

Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
---------------------------	--------------

Lifespan

Average Rated Life (hr)	11000
-------------------------	-------

Capabilities

Dimming	No
---------	----

Certificates & Standards

Certification Listing	RoHS / CSA / FTC / FCC / cULus
-----------------------	--------------------------------

Country-specific categorizations

Order reference	LED9PAR30LN830F
-----------------	-----------------

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	E26
Length	113.51 mm
Height	95.00 mm
Width	95.00 mm

Safety advice

- Not for use in totally enclosed fixtures.
- Suitable for use in UL rated fixture where protected from the weather.
- Non-dimmable.
- -4°F to +104°F (-20°C to +40°C)
- Not for use with emergency light fixtures or exit lights.

DOWNLOAD DATA

Spec Sheets and Product Documents	Document name
 Product Family Spec Sheet	Contractor Series LED PAR Lamps

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.