

Project:

Type:

Prepared By:

Date:



UPC: 192552028707

Features and Benefits

- Replaces traditional metal halide or high pressure sodium HID lamp
- Adjustable CCT allows for in-field customization
- Integral driver enables lamp to be wired directly to line voltage without need for an external driver or ballast
- Rated for use in enclosed fixtures in dry or damp locations
- AUX port for integrating individual, lamp-level controls

Technical Specifications

Performance

Product Type:
HID Replacement

Description:
CCT field adjustable horizontal and expandable LED lamps that make great replacements for high output area lights

Wattage Equivalency:
400W Metal Halide

Input Wattage:
110W

Lumens:
15,400/16,500/15,950lm

Efficacy:
140/150/145lm/W

L70 Lifespan:
50,000-Hour LED lifespan based on IES LM-70 results

Electrical

THD:
≤20%

Power Factor:
≥0.9

Dimmable:
Yes

Input Voltage:
100-277V

Operating Frequency:
50/60Hz

Input Current @ 120V (mA):
945mA

Input Current @ 240V (mA):
504mA

Input Current @ 277V (mA):
441mA

Operating Temperature:
-22°F to 140°F (-30°C to 60°C)

Flicker:
<30%

Surge Protection:
4kV

LED Characteristics

Color Temperature:
Field adjustable via dip switch 3000/4000/5000K

Color Accuracy (CRI):
≥80 CRI

R9 Value:
High color performance with R9 no greater than 0

Color Consistency:
<6-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color

Color Stability:
LED color temperature is warrantied to shift no more than 200K in color temperature over a 5-year period

Technical Specifications (continued)**Color Uniformity:**

RAB's range of Correlated Color Temperature follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2017.

Installation**Installation Method:**

UL Type B, Ballast Bypass

Installation Orientation:

Horizontal

Base Type:

EX39 Exclusionary Mogul

Construction**Finish:**

Clear

Bulb Shape:

Post Top

Endcap Material:

Metal

Enclosure Material:

Polycarbonate

Compliance**Listings:**

UL Listed, UL Classified

Environment:

Suitable for use in dry and damp environments

Fixture Rating:

Suitable for use in enclosed fixtures

IP Rating:

IP64

Energy Star Approved:

No.

There is no product category on Energy Star for this lamp to qualify under.

Certification Model Number:

H20045(HIDFA-110-H-EX39-8CCT-BYP/5SP)

T20 Compliant:

Not compliant

California Title 24 JA8 Compliant:

Not Compliant

California Energy Commission (CEC) Status:

Lawful for Sales in California

RoHS:

Mercury and UV free. RoHS-compliant components.

FCC:

Complies with Part 15B of the FCC Rules

Other**Accessories:**

[XFMR200-480-277](#)

Transformer 200W 480V

[SP10KV](#)

10 kV Surge protector

\

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	6	17.52	13.27	14
PALLET	144	45.28	35.43	41.34

Dimension

