

Project: Type: Prepared By: Date:



Features and Benefits

 ${\it Energy-efficient \, replacement \, for \, incandescent \, and \, halogen \, lamps}$

Durable plastic construction reduces risk of breakage

Rated for use in enclosed and open fixtures in dry or damp locations Frosted lens delivers smooth, diffuse light

 $Longer\ lifespan\ compared\ to\ legacy\ equivalents\ minimizes\ replacement\ and\ maintenance\ costs$

Technical Specifications

Performance

Product Type:

A-Line 80CRI Non Dimmable

Description:

Replace conventional general purpose bulbs in open or enclosed fixtures in dry or damp environemnts.

Wattage Equivalency:

40W Incandescent

Input Wattage:

6W

Lumens (Nominal):

450lm

Efficacy:

75lm/W

L70 Lifespan:

15,000-Hour LED lifespan based on IES LM-70 results

Electrical

Power Factor:

≥0.6

Dimmable:

No

Input Voltage:

120V

Operating Frequency:

60 Hz

Input Current @ 120V (mA):

60mA

Operating Temperature:

-13°F to 113°F (-25°C to 45°C)

Optical

Beam Angle:

230°

LED Characteristics

Color Temperature:

2700K

Color Accuracy (CRI):

≥80 CRI

R9 Value:

High color performance with R9 no greater than 0

Color Consistency:

<7-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color

Construction

Base Type:

E26 Edison

Finish:

White

Bulb Shape:

A19

Endcap Material:

Nickel-Aluminum

Enclosure Material:

Plastic

Technical Specifications (continued)

Lens Finish:

Frosted

Compliance

Listings:

UL Listed

Environment:

Suitable for use in dry and damp environments

Fixture Rating:

Suitable for use in enclosed fixtures

Energy Star Approved:

This product is ENERGY STAR® Version 2.2 Certified

T20 Compliant:

Not Compliant

California Title 24 JA8 Compliant:

Not Compliant

California Energy Commission (CEC) Status:

Not Lawful for Sales in California

RoHS:

Mercury and UV free. RoHS-compliant components.

FCC:

Complies with Part 15B of the FCC Rules

Other

Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of three (3) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Note:

All values are typical (tolerance +/- 10%)

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	12	10	7.6	5
PALLET	3456	45.4	40	46.1



