



Weight: 10.1 lbs

Type:

Date:

LED Info

Type	Constant Current	Watts	52W
120V	0.48A	Color Temp	3000K (Warm)
208V	0.30A	Color Accuracy	82 CRI
240V	0.26A	L70 Lifespan	100,000 Hours
277V	0.22A	Lumens	4,285 lm
Input Watts	59W	Efficacy	72.6 lm/W

Suitable for wet locations

100,000-Hour LED lifespan based on IES LM-80 results and TM-21 calculations

3 mounting stems included. 6", 12" and 18" can be combined to achieve a maximum length of 36". 42' of wire supplied. The pendants thread into a hang-straight, leveling the fixture. Pendant outside diameter is 3/4. Threads are 1/4. Circular canopy included.

Cast aluminum Thermal Management system for optimal heat sinking. The PLED is designed for cool operation, most efficient output and maximum LED life by minimizing LED junction temperature.

Precision die-cast aluminum housing, lens frame

Formulated for high durability and long-lasting color

Mercury and UV free. RoHS-compliant components.

Suitable for use in up to 40°C (104°F)

The minimum starting temperature is -40°C (-40°F)

The LED will deliver 70% of its initial lumens at 100,000 hours of operation

7-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color

LED color temperature is warranted to shift no more than 200K in color temperature over a 5-year period

RAB's range of Correlated Color Temperature follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2017.

The PLED design is protected by U.S. PATENT D608,040 and patents pending in the U.S., Canada, China, Taiwan and Mexico.

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

This product complies with the 52.225-21 "Required Use of American Iron, Steel, and Manufactured Goods-- Buy American Act-- Construction Materials (October 2010).

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

B2 U1 G1

Electrical

Multi-chip 26W high output long life LED Driver
Constant Current, 720mA, Class 2, 6kV Surge
Protection, 100V-277V, 50-60 Hz, 100-240V.4 Amps.

[illegible]

Die cast aluminum lens frame with tempered glass and double gasketing
Fully Shielded, Full Cutoff Optics
LED Light Engine life delivers 70% of rated lumens at 100,000-hours
5-Year, No-Compromise Warranty