



Project: Type:

Prepared By: Date:

Square steel poles drilled for 2 Area Lights at 180°. Designed for ground mounting. Poles are stocked nationwide for quick shipment. Protective packaging ensures poles arrive at the job site good as new.

Color: Bronze

Weight: 319.0 lbs

# **Technical Specifications**

#### Compliance

#### CSA Listed:

Suitable for wet locations

#### Construction

## Shaft:

46,000 p.s.i. minimum yield.

### **Hand Holes:**

Reinforced with grounding lug and removable cover

#### **Base Plates:**

36,000 p.s.i. minimum yield.

#### **Shipping Protection:**

All poles are shipped in individual corrugated cartons to prevent finish damage

## Color:

Bronze powder coating

#### Height:

25 ft

### Gauge:

7

## Wall Thickness:

3/16"

## **Shaft Size:**

5

#### **Hand Hole Dimensions:**

3" x 5"

## **Bolt Circle:**

11"

#### **Base Dimension:**

11"

## Weight:

319 lbs

## **Anchor Bolt:**

Galvanized anchor bolts and galvanized hardware and anchor bolt template. All bolts have a 3" hook.

## **Anchor Bolt Templates:**

WARNING Template must be printed on 12" x 18" sheet for actual size. CHECK SCALE BEFORE USING. Templates shipped with anchor bolts and available online.

## **Pre-Shipped Anchor Bolts:**

Bolts can be pre-shipped upon request for additional freight charge

## Max EPA's/Max Weights:

70MPH 17.2 ft/625 lb. 80MPH 11.1 ft/625 lb. 90MPH 6.9 ft/625 lb. 100MPH 3.9 ft/625 lb. 110MPH 1.7 ft/625 lb. 120MPH 0.1 ft/620lb

## Other

#### Terms of Sale:

Pole Terms of Sale is available online.

### **Buy American Act Compliance:**

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

PS5-07-25D2

