

LTRL SERIES

Commercial Lighting

WESTGATE

THE FUTURE IS HERE...AND IT'S QUITE BRIGHT!

LTRL-2X2-MCTP4

ARCHITECTURAL ADVANCED BLADE DESIGN TROFFER



Multi Color Temperature &
Multi Power/Wattage (Selectable)




The Architectural Advanced Blade Design Troffer is a high-performance lighting fixture designed for modern interiors. Featuring an innovative blade-style diffuser, it delivers uniform, glare-free illumination while enhancing architectural aesthetics. Ideal for commercial and office spaces, this troffer offers energy efficiency, sleek design, and advanced optical control for optimal lighting distribution.

Customer Name: _____

Project Name: _____

Note: _____

Type: _____



23.75"(L) x 23.75"(W) x 4.17"(H)

Features

- 5-Year Warranty
- White Finish
- Rated Life: 50,000 Hours
- Multi CCT & Power
(Selectable Switch On Back Of Fixture)

Technical Specifications

Electrical:

- Voltage: 120-277V AC 50/60Hz
- Wattage: 30W/40W/50W
- Power Factor: >0.97
- Efficacy: 115 LPW

Mechanical:

- White Finish
- Cold-Rolled Steel
- Earthquake Hooks Built Into The Housing
- Operating Temperature: -4°F ~ 122°F
- 5-Year Warranty

Lighting:

- Multi CCT & Power
(Selectable Switch On Back Of Fixture)
- Dimmable: 0~10V Dimming
- LED Type: SMD 2835
- Total Lumens: 3450LM/4600LM/5750LM
- Color Rendering Index: CRI ≥ 80
- Color Temperatures: 3000K/3500K/4000K/5000K
- Rated Life: 50,000 Hours

Applications:

- Commercial Offices – Provides uniform, glare-free lighting for a comfortable workspace.
- Educational Facilities – Enhances learning environments with efficient and visually appealing illumination.
- Healthcare Settings – Delivers high-quality lighting that supports visibility and comfort.
- Retail Spaces – Enhances product displays with well-distributed, stylish lighting.
- Hospitality & Lobbies – Creates an inviting ambiance with architectural aesthetics.

Other Models:

- 72W | 8280LM | LTRL-2X4-MCTP4





Phone: (877) 805-2252 | Fax: (877) 805-2252
www.westgatemfg.com |




WG-3112025

Photometrics: LTRL-2X2-MCTP4



BUG Rating: B1-U3-G1



Other Views:



Side View



Front View

Performance Table: LTRL-2X2-MCTP4

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
LTRL-2X2-MCTP4	30W 40W 50W	120~277V	3450LM 4600LM 5750LM	3000K 3500K 4000K 5000K	B1-U3-G1	115

Sample Ordering

Model	Size	Watt/Color Temp.
LTRL	2X2	MCTP

Factory-Installed Options:

Blank = No Option For Accessories
 OPT-EM-LTRL= EMERGENCY BACKUP BATTERY MOUNTED ON TOP OF FIXTURE
 OPT-FWH-63= 6FT 3-WIRE WHIP
 OPT-FWH-65= 6FT 5-WIRE WHIP
 OPT-FWH-66= 6FT 6-WIRE WHIP
 OPT-SEN-3MRLV-5=PROGRAMMABLE MICROWAVE BI-LEVEL SENSOR

BUILT-IN SWITCH:



MULTI-CCT & WATTAGE

FACTORY-INSTALLED OPTIONS:



OPT-EM-LTRL



OPT-SEN-3MRLV-5



OPT-FWH-63
 OPT-FWH-65
 OPT-FWH-66

